



GSE-26X

HIGH REBOUND

LOW SHRINKAGE RATE

NICE COMPRESSION SET PERFORMANCE



PROPERTIES

Property	Unit	Standard	Value
MI (190°C@2.16kg)	g/10min	ASTM D1238	1.0
Density	g/cm ³	ASTM D792	0.95 - 1.10
Hardness	Shore A	ASTM D2240	68±2
Tensile Strength	kg/cm ²	ASTM D638	96
Elongation	%	ASTM D638	790
Tear Strength	kg/cm	ASTM D624	48
Softening Point	°C	ASTM D1525	100 - 105

All given data should be considered as a reference guide.

FORMS

1. Form: Pellets
2. Color: Natural (White)
3. Packaging: 25 kg/bag



FEATURES

1. Highly compatible with all kinds of rubber and plastics.
2. Suitable for peroxide crosslink system.
3. It's excellent with adhesive property and resilience.
4. Produce products with physical properties similar to natural rubber and synthetic rubber foaming products, and also is recyclable and has low shrinkage rate and enhances compression set.

APPLICATIONS

Sports and leisure, footwear soles, safety protection products and other products which acquires high rebound and good compression set.

CERTIFICATIONS

SGS 8 Heavy Metals Free, Report No. TE/2020/10016

STORAGE

1. Keep in cool place without being exposed to direct sunlight. Store it at temperature below 50°C.
2. Keep out of fire and heat.
3. For better storage, keep the packaging sealed if unused up.

Version 2. 2020.01.02