



GSE-46

HEAT SHRINKAGE PROOF
HIGH REBOUND
ENHANCE COMPRESSION SET




PROPERTIES

Property	Unit	Standard	Value
MI(190°C@2.16kg)	g/10min	ASTM D1238	4.0~5.5
Density	g/cm ³	ASTM D792	0.95~1.10
Hardness	Shore A	ASTM D2240	60±2
Tensile Strength	kg/cm ²	ASTM D412	27
Elongation	%	ASTM D412	1219
Tear Strength	kg/cm	ASTM D624	21
Softening Point	°C	ASTM D1525	100-110

FORMS

1. Form: Pellets
2. Color: Natural (White)
3. Packaging: 25 kg/bag



FEATURES

1. Rubber-like elasticity and great touching feels.
2. The adhesive ability will not be effected by increased in amount used.
3. Can be applied with EVA, LDPE, POE, and EPDM etc. to achieve different product properties.
4. Improves heat shrinkage resistance ability, creates better compression set performance, and elevate rebounding ability of the foam products.
5. VG-301(Victory General) additive is recommend for adding coordinately.

APPLICATIONS

Mats, footwear materials, packaging materials.

CERTIFICATIONS

1. SGS 8 Heavy Metal free, Report TE/2015/40265A1
2. SGS PAHs & 14P free, Report TE/2015/40265A1

STORAGE

1. Keep in cool place without being exposed to direct sunlight. Store it at temperature below 50°C.
2. Keep out of fire and heat.
3. For better storage, keep the packaging sealed if unused up.