



VICTORY GENERAL TECHNOLOGY CO.
High Tech Rubber & Plastic Material Manufacturer

GSE-27X *TPE MODIFIER* *HIGH REBOUND*



PROPERTIES

Property	Unit	Standard	Value
MI(190°C@2.16kg)	g/10min	ASTM D1238	1.0~2.0
Density	g/cm ³	ASTM D792	0.95~1.05
Hardness	Shore A	ASTM D2240	62±2
Tensile Strength	kg/cm ²	ASTM D412	37
Elongation	%	ASTM D412	690
Tear Strength	kg/cm	ASTM D624	26
Softening Point	°C	ASTM D1525	105-110

FORMS

1. Form: Pellets
2. Color: Natural (White)
3. Packaging: 25 kg/bag



FEATURES

1. GSE-27X owns excellent rebound and adhesivity.
2. GSE-27X is highly compatible with various rubber and plastics.
3. GSE-27X can be applied to peroxide DCP crosslink system.
4. GSE-27X makes the physical properties like natural rubber and synthetic rubber foaming products.
5. GSE-27X is recyclable.

APPLICATIONS

Sports and leisure, footwear, safety protection, medical care and other products which acquires high rebound and good compression set.

STORAGE

1. Keep in cool place without being exposed to direct sunlight. Store it at temperature below 50°C.
2. Keep out of fire and heat.
3. For better storage, keep the packaging sealed if unused up.