



GSE-26X

HIGH REBOUND
LOW SHRINKAGE RATE
NICE COMPRESSION SET
PERFORMANCE



PROPERTIES

Property	Unit	Standard	Value
MI(190°C@2.16kg)	g/10min	ASTM D1238	1.1~1.5
Density	g/cm ³	ASTM D792	1.0~1.10
Hardness	Shore A	ASTM D2240	68±2
Tensile Strength	kg/cm ²	ASTM D412	56
Elongation	%	ASTM D412	640
Tear Strength	kg/cm	ASTM D624	44
Softening Point	°C	ASTM D1525	105-110

FORMS

1. Form: Pellets
2. Color: Natural (White)
3. Packaging: 25 kg/bag



FEATURES

1. Highly compatible with all kinds of rubber and plastics.
2. Suitable for peroxide crosslink system.
3. It's excellent with adhesive property and resilience.
4. Produce products with physical properties similar to natural rubber and synthetic rubber foaming products, and also is recyclable and has low shrinkage rate which rubber foam doesn't have.

APPLICATIONS

Sports and leisure, footwear, safety protection, medical care and other products which acquires high rebound and good compression set.

STORAGE

1. Keep in cool place without being exposed to direct sunlight. Store it at temperature below 50°C.
2. Keep out of fire and heat.
3. For better storage, keep the packaging sealed if unused up.