



GSE-27X TPE MODIFIER HIGH REBOUND



PROPERTIES

Property	Unit	Standard	Value
MI (190°C@2.16kg)	g/10min	ASTM D1238	1.0 - 2.0
Density	g/cm ³	ASTM D792	0.95 - 1.05
Hardness	Shore A	ASTM D2240	62±2
Tensile Strength	kg/cm ²	ASTM D638	37
Elongation	%	ASTM D638	690
Tear Strength	kg/cm	ASTM D624	26
Softening Point	°C	ASTM D1525	105 - 110

All given data should be considered as a reference guide.

FORMS

1. Form: Pellets
2. Color: Natural (White)
3. Packaging: 25 kg/bag



FEATURES

1. GSE-27X owns excellent rebound and adhesivity.
2. GSE-27X is highly compatible with various rubber and plastics.
3. GSE-27X can be applied to peroxide DCP crosslink system.
4. GSE-27X makes the physical properties like natural rubber and synthetic rubber foaming products.
5. GSE-27X is recyclable.

APPLICATIONS

Sports and leisure, footwear soles, safety protection products and other products which acquires high rebound and good compression set.

CERTIFICATIONS

SGS 8 Heavy Metals Free, Report No. TE/2020/10017

STORAGE

1. Keep in cool place without being exposed to direct sunlight. Store it at temperature below 50°C.
2. Keep out of fire and heat.
3. For better storage, keep the packaging sealed if unused up.